

light-shielding film overlapping the orientation divider in the region other than the space region along an extension direction of the orientation divider.

Rewrite claim 11 as follows:

11. (Amended) A liquid crystal display device for displaying by controlling the orientation of a liquid crystal by means of a plurality of pixel electrodes formed for each pixel and an opposing electrode disposed to oppose the plurality of pixel electrodes with the liquid crystal therebetween, comprising:

an orientation divider for dividing an orientation direction of the liquid crystal in a single pixel into a plurality of directions; and

a light-shielding film which is disposed to overlap with boundaries of the orientation directions of the liquid crystal formed by the orientation divider;

wherein the liquid crystal has a negative anisotropy of dielectric constant, and a vertical orientation film is formed to cover the pixel electrodes; and

wherein the orientation divider has a width different from that of the light-shielding film.

Rewrite claims 15 as follows:

15. (Amended) A liquid crystal display device for displaying by controlling the orientation of a liquid crystal by means of a plurality of pixel electrodes formed for each pixel and an opposing electrode disposed to oppose the plurality of pixel electrodes with the liquid crystal therebetween, comprising:

an orientation divider for dividing an orientation direction of the liquid crystal in a single pixel into a plurality of directions, the orientation divider being provided in a space region between the pixel and an adjacent pixel and in a region other than the space region; and

a light-shielding film which is disposed to overlap with boundaries of

the orientation divider in the region other than the space region along an extension direction of the orientation divider.

20. (Amended) A liquid crystal display device for displaying by controlling the orientation of a liquid crystal by means of a plurality of pixel electrodes formed for each pixel and an opposing electrode disposed to oppose the plurality of pixel electrodes with the liquid crystal therebetween, comprising:

an orientation divider for dividing an orientation direction of the liquid crystal in a single pixel into a plurality of directions; and

a light-shielding film which is disposed to overlap with boundaries of the orientation directions formed by the orientation divider, the light-shielding film being a conductive material;

wherein the liquid crystal has a negative and anisotropy of dielectric constant, and a vertical orientation film is formed to cover the pixel electrodes;

wherein the orientation divider has a width different from that of the light-shielding film.

Rewrite claim 24 as follows:

24. (Amended) A liquid crystal display device, characterized in that:

liquid crystal is sealed between a first substrate and a second substrate which are disposed so as to oppose each other;

the first substrate has switching elements connected to gate signal lines and drain signal lines, pixel electrodes which are connected to the switching elements and made of a conductive material and a vertical orientation film for orienting the liquid crystal;

the second substrate has an opposing electrode which has orientation control windows at positions overlapping with the pixel electrodes to control the

the drain signal lines are disposed on the first substrate at positions that overlap with the orientation control window; and

the orientation control windows include a region which extends in a predetermined direction and the drain signal lines are disposed to overlap the extension region along the longitudinal direction of the extension region.

Rewrite claim 25 as follows:

25. (Amended) A liquid crystal display device, characterized in that:

liquid crystal is sealed between a first substrate and a second substrate which are disposed so as to oppose each other;

the first substrate has switching elements connected to gate signal lines and drain signal lines, pixel electrodes which are connected to the switching elements and made of a conductive material and a vertical orientation film for orienting the liquid crystal;

the second substrate has an opposing electrode which has orientation control windows at positions overlapping with the pixel electrodes to control the orientation of the liquid crystal and a vertical orientation film for orienting the liquid crystal;

the drain signal lines are disposed on the first substrate at positions that overlap with the orientation control windows; and

wherein the orientation control window has a width different from that of the drain signal line overlapping with the orientation control window.

Please add the following new claims:

--38. (New) A liquid crystal display device for displaying by controlling the orientation of a liquid crystal by means of a plurality of pixel electrodes formed for each pixel and an opposing electrode disposed to oppose the plurality of pixel electrodes with the liquid crystal therebetween, comprising:

an orientation divider for dividing an orientation direction of the liquid crystal in a single pixel into a plurality of directions; and

a light-shielding film which is disposed to overlap with boundaries of the orientation directions of the liquid crystal formed by the orientation divider;

wherein the light-shielding film is the drain signal line.

39. (New) A liquid crystal display device for displaying by controlling the orientation of a liquid crystal by means of a plurality of pixel electrodes formed for each pixel and an opposing electrode disposed to oppose the plurality of pixel electrodes with the liquid crystal therebetween, comprising:

an orientation divider for dividing an orientation direction of the liquid crystal in a single pixel into a plurality of directions;

a light-shielding film which is disposed to overlap with boundaries of the orientation directions of the liquid crystal formed by the orientation divider; and

an orientation divider extending in a predetermined direction is provided on the side of the opposing substrate and a light-shielding film is disposed to overlap the divider along the extension direction of the divider. --